

Takumi UC250

Ref: TAKUMI UC250



Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Tech specs

Brand	TAKUMI & HURCO
Axes	4 + 1
X Axis stroke	860
Y Axis travel	520
Z Axis stroke	610
Spindle nose to table surface	65 - 675
Table diameter (Ø)	Ø255
Max. Load (Workpiece Load)	200
T slot (WxDxN)	4x12-90
Spindle type	Direct drive
Spindle Speed	15.000
Main motor	9/ 15 (S3-25%)
Spindle Nose	BBT40
Lubrication method of the main spindle	Grease
Cutting Feedrate	36/ 36/ 36
X/Y/Z Axis cutting feedrate	12.000
C Axis rotation	360
Positioning accuracy of the C axis	±10
Max speed C axis	25
C Axis rated torque	342
Rotation angle of the A axis	+30 -110
Positioning accuracy of the A axis	±10
A axis velocity	16.6
A Axis rated torque	720
Auto tool changer ATC type	Swing-Arm
Tool storage capacity	24
Max. Tool Diameter	75/ 120
Max. Tool Length	250
Max. Tool Weight	7
Pneumatic pressure	6
Power requirement	40
Coolant tank capacity	300
Machine weight	6.700
Floor space (LxW)	2.160x2.660
Machine Height	3.300

Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Images

