

Takumi UC400

Ref: TAKUMI UC400



Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Tech specs

Brand	TAKUMI & HURCO
Axes	4 + 1
X Axis stroke	1067
Y Axis travel	610
Z Axis stroke	520
Spindle nose to table surface	90 - 610
Table diameter (Ø)	Ø400
Max. Load (Workpiece Load)	250
T slot (WxDxN)	8x12-45
Spindle type	Direct drive
Spindle Speed	15.000
Main motor	9/ 15 (S3-25%)
Spindle Nose	BBT40
Lubrication method of the main spindle	Grease
Cutting Feedrate	36/ 36/ 36
X/Y/Z Axis cutting feedrate	12.000
C Axis rotation	360
Positioning accuracy of the C axis	±10
Max speed C axis	22.2
C Axis rated torque	540
Rotation angle of the A axis	+30 -110
Positioning accuracy of the A axis	±10
A axis velocity	22.2
A Axis rated torque	2880
Auto tool changer ATC type	Swing-Arm
Tool storage capacity	24
Max. Tool Diameter	75/ 120
Max. Tool Length	250
Max. Tool Weight	7
Pneumatic pressure	6
Power requirement	60
Coolant tank capacity	400
Machine weight	7.500
Floor space (LxW)	2.250x3.200
Machine Height	3.100

Images

