

Takumi U400

Ref: TAKUMI U400



Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Tech specs

Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Brand	TAKUMI & HURCO
Axes	5
X Axis stroke	550
Y Axis travel	950
Z Axis stroke	500
Spindle nose to table surface	90 - 590
Table diameter (Ø)	Ø 398
Max. Load (Workpiece Load)	250
T slot (WxDxN)	6x14-60
Spindle type	Direct drive
Spindle Speed	15.000
Main motor	10/ 14 (S6-40%)
Spindle Nose	BBT40
Lubrication method of the main spindle	Oil-air
Cutting Feedrate	36/ 36/ 36
X/Y/Z Axis cutting feedrate	20.000
C Axis rotation	360
Positioning accuracy of the C axis	±5
Max speed C axis	25
C Axis rated torque	756
Rotation angle of the A axis	+30 -110
Positioning accuracy of the A axis	±5
A axis velocity	25
A Axis rated torque	756
Auto tool changer ATC type	Swing-Arm
Tool storage capacity	30
Max. Tool Diameter	75/ 150
Max. Tool Length	300
Max. Tool Weight	7
Pneumatic pressure	6
Power requirement	60
Coolant tank capacity	340
Machine weight	9.100
Floor space (LxW)	3.000x2.560
Machine Height	3.170

Images

