

Takumi U800

Ref: TAKUMI U800



Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Tech specs

Brand	TAKUMI & HURCO
Axes	5
X Axis stroke	800
Y Axis travel	1150
Z Axis stroke	750
Spindle nose to table surface	125 - 875
Table diameter (Ø)	Ø800
Max. Load (Workpiece Load)	1000
T slot (WxDxN)	14x100x7
Spindle type	Built-in
Spindle Speed	20.000
Main motor	25/ 40 (S6-40%)
Spindle Nose	HSK-A63
Lubrication method of the main spindle	Oil - air
Cutting Feedrate	48/ 48/ 48
X/Y/Z Axis cutting feedrate	24.000
C Axis rotation	360
Positioning accuracy of the C axis	±5
Max speed C axis	100
C Axis rated torque	1870
Rotation angle of the A axis	±120
Positioning accuracy of the A axis	±5
A axis velocity	80
A Axis rated torque	1870x2
Auto tool changer ATC type	Flat type
Tool storage capacity	32
Max. Tool Diameter	90/ 125
Max. Tool Length	300
Max. Tool Weight	7
Pneumatic pressure	6
Power requirement	80
Coolant tank capacity	540
Machine weight	18.000
Floor space (LxW)	4.200x3.055
Machine Height	4.100

Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Images

