

Takumi U600

Ref: TAKUMI U600



Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Tech specs

Brand	TAKUMI & HURCO
Axes	5
X Axis stroke	660
Y Axis travel	1020
Z Axis stroke	500
Spindle nose to table surface	160 - 660
Table diameter (Ø)	Ø 600
Max. Load (Workpiece Load)	500
T slot (WxDxN)	14x100x7
Spindle type	Direct drive
Spindle Speed	15.000
Main motor	10 / 14 (S6-40%)
Spindle Nose	BBT40
Lubrication method of the main spindle	Aire - aceite
Cutting Feedrate	36/ 36/ 36
X/Y/Z Axis cutting feedrate	20.000
C Axis rotation	360
Positioning accuracy of the C axis	±5
Max speed C axis	33
C Axis rated torque	466
Rotation angle of the A axis	A-axis +30 -110
Positioning accuracy of the A axis	A-axis ±5
A axis velocity	25
A Axis rated torque	1487
Auto tool changer ATC type	Swing-Arm
Tool storage capacity	40
Max. Tool Diameter	75/ 150
Max. Tool Length	300
Max. Tool Weight	7
Pneumatic pressure	6
Power requirement	60
Coolant tank capacity	560
Machine weight	14.000
Floor space (LxW)	3.255x3.855
Machine Height	3.520

Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Images

