

Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

MACHINING CENTER LAGUN GVC 1000

Ref: 043514



Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Tech specs

Brand	LAGUN
MODEL	GVC 1000
CONTROL	HEIDENHAIN 426
TABLE DIMENSIONS	1200 x 500
TRAVELS X, Y, Z	(X) 1000, (Y) 500, (Z) 620
TAPER	BT 40
RPM HEADSTOCK	6.000
TOOL CHANGER	18 POSICIONES
CHIP EXTRACTOR	SI
YEAR	2002
EXTERNAL DIMENSIONS	2.240 X 2.930 X 2.750
WEIGHT	6.300

Images



AUTOMATIC TOOL CHANGING DEVICE	GVC 1000
Number of Tools	18
Selection System	NO RANDOM; TWO-DIRECTIONAL
Ø Maximum (adjacent tools)	85 mm
Ø Maximum (alternate tools)	135 mm
Maximum Tool Length	250 mm
Admissible Max. Weight for 1 st Tool	8 kg
Admissible Max. Weight for all the tools	80 kg
Toolholder (standard)	MAS-403-BT40
Toolholder (optional)	ISO-40 7388/1 DIN 95871-A
Drawer for Tool Clamping (standard)	MAS-P40T-1
Drawer for Tool Clamping (optional)	ISO 7388/2-A DIN 95872-A
Tool Replacement Time	0 sec
Required Air Pressure	6-7 kg/cm ²
GENERAL INFORMATION	
Machine Height	2.750 mm
Machine Width	2.030 mm
Machine Depth	2.240 mm
Net machine weight	6.000 kg
Gross Machine Weight	6.300 kg
Total Installed Power	22 kW

TABLE	GVC 1000
Table Surface	1200 x 800 mm
Number and Width of T-slots	3 x 20 x 120 mm
Table height from floor	810 mm
Ball screws (X-Y)	Ø 40 x 18 mm
MOVEMENTS AND CAPACITY	
Longitudinal Movement (X axis)	1600 mm
Cross Movement (Y axis)	900 mm
Vertical Movement (Z axis)	510 + 111.5 mm
Ballbars - Spindle to Table	108 - 618 (21/3) mm
Distance Table Centre to Column	260 - 760 mm
Distance Spindle Centre to Column	810 mm
Maximum Load Capacity	780 kg
HEADSTOCK	
Spindle nose taper (standard)	MAS-403-BT40
Spindle nose taper (optional)	ISO-40 7388/1 DIN 95871-A
Speed range (standard)	30 - 6000 r.p.m.
Speed range (optional)	100 - 10000 r.p.m.
Number of Spindles	Infinite Variable
Main Motor Power (AC input)	11.13 kW
Ballbearings (Z-axis)	Ø 40 x 18 mm
FEED	
Cutting Speed	According CNC type
Longitudinal and Cross Rapid Movement (X-Y)	20.000 mm/min
Vertical Rapid Movement (Z)	12.000 mm/min
MACHINE ACCURACY	
Positioning	± 0.008 mm
Repeatability	± 0.008 mm
Resolution	± 0.001 mm
MOTORS	
Main Spindle (headstock) Alternating Current	11.13 kW
Scale 9/10/20/3/5	2.30 kW
V-axis 40/30/40/3/5	2.78 kW
	8 kW
	8 kW
	3.5 kW

