

## CENTRO MECANIZADO LAGUN GVC 1000

Ref: 043514



**Central**

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Teléfono: +34 966 662 296 / FAX: +34 966 663 856

**Delegación IBI**

Avda. de la provincia, 73

03440 IBI (Alicante)

Teléfono: +34 965 553 233 / FAX: +34 966 554 990

## Especificaciones técnicas

<b>Marca</b>	LAGUN
<b>MODELO</b>	GVC 1000
<b>CONTROL</b>	HEIDENHAIN 426
<b>DIMENSIONES DE LA MESA</b>	1200 x 500
<b>RECORRIDOS X, Y, Z</b>	(X) 1000, (Y) 500, (Z) 620
<b>CONO</b>	BT 40
<b>RPM CABEZAL</b>	6.000
<b>CAMBIADOR DE HERRAMIENTAS</b>	18 POSICIONES
<b>EXTRACTOR DE VIRUTAS</b>	SI
<b>AÑO</b>	2002
<b>MEDIDAS EXTERIORES</b>	2.240 X 2.930 X 2.750
<b>PESO</b>	6.300

**Central**

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Teléfono: +34 966 662 296 / FAX: +34 966 663 856

**Delegación IBI**

Avda. de la provincia, 73

03440 IBI (Alicante)

Teléfono: +34 965 553 233 / FAX: +34 966 554 990

## Equipamiento Estándar

---

Incluye 4º EJE

## Imágenes



AUTOMATIC TOOL CHANGING DEVICE	GVC 1000
Number of Tools	18
Selection System	NO RANDOM; TWO-DIRECTIONAL
Ø Maximum (adjacent tools)	85 mm.
Ø Maximum (alternate tools)	135 mm.
Maximum Tool Length	250 mm.
Admissible Max. Weight for 1 <sup>st</sup> Tool	8 kg.
Admissible Max. Weight for all the tools	90 kg.
Toolholder (standard)	MAS-403-BT40.
Toolholder (optional)	ISO-40 7388/1 DIN 95871-A.
Drawer for Tool Clamping (standard)	MAS-P40T-1.
Drawer for Tool Clamping (optional)	ISO 7388/2-A DIN 95872-A.
Tool Replacement Time	0 sec.
Required Air Pressure	6-7 kg./cm <sup>2</sup> .
<b>GENERAL INFORMATION</b>	
Machine Height	2.750 mm.
Machine Width	2.030 mm.
Machine Depth	2.240 mm.
Net machine weight	6.000 kg.
Gross Machine Weight	6.300 kg.
Total Installed Power	22 kW.

TABLE	GVC 1000
Table Surface	1200 x 800 mm.
Number and Width of T-slots	3 x 20 x 120 mm.
Table height from floor	810 mm.
Ball screws (X-Y)	Ø 40 x 18 mm.
<b>MOVEMENTS AND CAPACITY</b>	
Longitudinal Movement (X axis)	1600 mm.
Cross Movement (Y axis)	900 mm.
Vertical Movement (Z axis)	510 + 111.5 mm.
Ballbars - Spindle to Table	108 - 618 (21/3) mm.
Distance Table Centre to Column	260 - 760 mm.
Distance Spindle Centre to Column	810 mm.
Maximum Load Capacity	700 kg.
<b>HEADSTOCK</b>	
Spindle nose taper (standard)	MAS-403-BT40.
Spindle nose taper (optional)	ISO-40 7388/1 DIN 95871-A.
Speed range (standard)	30 - 6000 r.p.m.
Speed range (optional)	100 - 10000 r.p.m.
Number of Spindles	Infinite Variable
Main Motor Power (AC input)	11.13 kW.
Ballbearings (Z-axis)	Ø 40 x 18 mm.
<b>FEED</b>	
Cutting Speed	According CNC type
Longitudinal and Cross Rapid Movement (X-Y)	20.000 mm./min.
Vertical Rapid Movement (Z)	12.000 mm./min.
<b>MACHINE ACCURACY</b>	
Positioning	± 0.005 mm.
Repeatability	± 0.005 mm.
Resolution	± 0.001 mm.
<b>MOTORS</b>	
Main Spindle (headstock) Alternating Current	11.13 kW.
Slave 9R/9W/3.5S	2.38 kW.
Slave 4R/4W/3.5S	2.38 kW.
	8 kW.
	8 kW.
	3.5W.

